
































# Aquami Monoblock heat pump

AQM60X1 <sup>[R14]</sup>



## Device features

							
Environmentally friendly refrigerant R32	Efficient heating	Energy efficiency class at 35°C A+++	Energy efficiency class at 55°C A++	Maximum COP 4,95	Operating range down to -25°C	Supply water temperature of 65°C	Integrated USB port for updates
							
Energy meter	Smart Grid functionality	Twin rotary compressor	Integrated electric heater	Outdoor unit drip tray heater	Compressor crankcase heater	Easy installation and maintenance	Silent mode
							
Wired controller Wi-Fi module	Configurable daily schedules	Configurable weekly schedules	Vacation mode	Menu in English	Multilanguage menu	Integrated temperature sensor	Weather operating modes (climate curve)
							
2 heating control zones	Dedicated application	Disinfection	DHW circulation pump operation schedules	Maximum leaving water temperature of 60°C (in DHW mode)	Prepared to create a cascade system		

# Specification outdoor unit

Model			AQM60X1 R14
EAN Code			5905567602184
Power supply		V-Hz, Ø	220-240-50, 1f
Heating (A7/W35)	Capacity	kW	6,35
	Rated input	kW	1,28
	COP		4,95
Heating (A7/W45)	Capacity	kW	6,30
	Rated input	kW	1,70
	COP		3,70
Heating (A7/W55)	Capacity	kW	6,00
	Rated input	kW	2,03
	COP		2,95
Cooling (A35/W18)	Capacity	kW	6,50
	Rated input	kW	1,35
	EER		4,80
Cooling (A35/W7)	Capacity	kW	7,00
	Rated input	kW	2,33
	EER		3,00
Seasonal energy efficiency LWT at 35°C	SCOP <sup>(1)</sup>		4,95
	Rated heat output	kW	6,8
	Seasonal energy efficiency ratio (η <sub>s</sub> )	%	195
	Annual energy consumption	kWh	2845
	Seasonal space heating energy efficiency class <sup>(1)</sup>		A+++
Seasonal energy efficiency LWT at 55°C	SCOP <sup>(1)</sup>		3,52
	Rated heat output	kW	5,70
	Seasonal energy efficiency ratio (η <sub>s</sub> )	%	137,9
	Annual energy consumption	kWh	3343
	Seasonal space heating energy efficiency class <sup>(1)</sup>		A++
SEER	LWT at 7°C		5,34
	LWT at 18°C		8,21
Maximum overcurrent protection (MOP)		A	32
Minimum circuit amps (MCA)		A	27
Compressor		Type	Twin rotary inverter compressor DC
Fan	Type		Brushless DC motor / BLDC
	Quantity		1
Refrigerant	Type / GWP		R32 / 675
	Quantity	kg	1,4
		TCO <sub>eq</sub>	0,95
Power cables: indoor unit		pcs × mm²	3 × 6
Bracket spacing	(W1×W2×D)		638 x 379 x 401
Sound pressure level		dB(A)	47,5
Sound power level		dB(A)	58
Net dimensions	(W×D×H)	mm	1295×429×718
Gross dimensions	(W×D×H)	mm	1375×475×885
Net weight / Gross weight		kg	91/112
Operating outdoor temperature	Cooling	°C	-5-43
	Heating	°C	-25-35
	DHW	°C	-25-43
Operation modes			Heating and cooling
Leaving water temperature	Space cooling	°C	5-25
	Space heating	°C	25-65
	DHW (tank)	°C	30-60
Electric heater	Power supply	V-Hz, Ø	220-240-50, 1f
	Number of heating stages / Power	pcs / kW	1 / 3
	Maximum operating current	A	13,5
Water circuit	Water connections		33mm (G1" BSP) external
	Pressure relief valve		0,3
	Condensate drain		16
	Expansion tank	Total volume / Actual volume	l
		Maximum pressure / Initial pressure	MPa
	Heat exchanger	Type	PHE / plate heat exchanger
		Minimum flow	l/min
	Water pump head		9
	Water pump type		DC
	Total water volume		3,2

(1) Seasonal energy efficiency class measured under average climate conditions.

Notes: DHW - Domestic hot water, LWT - Leaving water temperature

The sound pressure level is measured 1m in front of the unit and (1+H)/2m (where H is the height of the unit) above the floor in semi-anechoic room. During on-site operation sound pressure levels can be higher as a result of ambient noise. Sound pressure level and sound power level reflect the maximum value tested under three conditions specified respectively in notes A7W35, ΔT=5; A7W45, ΔT=5; A7W55 ΔT=8; relative humidity 85%. The figures specified above refer to the following standards: EN14511; EN14825; EN50564; EN12102; (EU) Np. 811/2013; (EU) No. 813/2013; Journal of Laws 2014 / C 207/02: 2014.